

139 68 PCT

(2)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 May 2001 (10.05.2001)


PCT

(10) International Publication Number  
WO 01/32456 A2

- |   |  |
|---|--|
| <p>(51) International Patent Classification<sup>7</sup>: B60J 5/00</p> <p>(21) International Application Number: PCT/US00/41661</p> <p>(22) International Filing Date: 27 October 2000 (27.10.2000)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data:<br/>09/433,912 3 November 1999 (03.11.1999) US</p> <p>(71) Applicant: THE BUDD COMPANY [US/US]; 3155 West Big Beaver Road, Troy, MI 48084 (US).</p> <p>(72) Inventors: PACELLA, John, P.; 2997 Rhineberry, Rochester Hills, MI 48309 (US). MROZOWSKI, Joseph,</p> | <p>E.; 6852 North Crest Way East, Clarkston, MI 48346 (US).<br/>MERCIER, Larry, A., Jr.; 6430 Dewey Drive, Troy, MI 48098 (US).</p> <p>(74) Agents: SCHIVLEY, G., Gregory et al.; Harness, Dickey &amp; Pierce, P.L.C., P.P. Box 828, Bloomfield Hills, MI 48303 (US).</p> <p>(81) Designated States (<i>national</i>): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.</p> <p>(84) Designated States (<i>regional</i>): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European</p> |
|---|--|

[Continued on next page]

(54) Title: MODULAR DOOR



(57) Abstract: A door includes a door shell coupled to a door module. The door shell includes an outer panel secured to an inner panel, the inner panel having an opening therein. The door shell defines a hollow cavity. The door module includes a cassette and an interior trim panel coupled to the cassette. The door module further includes an attachment mechanism for securing the door module to the door shell. The attachment mechanism is visually hidden during normal operation of the door. The cassette is cooperative with the inner panel to provide a positive rest position prior to securing the door module to the door shell.

WO 01/32456 A2

WO 01/32456 A2



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *Without international search report and to be republished upon receipt of that report.*

## MODULAR DOOR

### BACKGROUND OF THE INVENTION

#### 1. Technical Field

The present invention generally relates to motor vehicles, and more particularly, to a modular door for a motor vehicle.

#### 2. Discussion

Manufacturers of motor vehicles have long been faced with the difficult task of constructing a door which not only provides easy ingress and egress but also performs a variety of other functions such as mounting a window, a window regulator mechanism and other door hardware. Conventionally, vehicle doors include an inner panel and an outer panel fixed together about their edges to form a hollow shell in the interior lower portion thereof. The inner panel typically includes relatively small access apertures for permitting the insertion of hardware such as the window regulator mechanism and a door actuation device. However, the insertion and subsequent attachment of the door hardware tends to be a time consuming process that is inconvenient for the vehicle door assembler and costly to the vehicle manufacturer.

Previous attempts to reduce the time required for door assembly have failed to produce satisfactory results particularly with regard to the appearance and structure of the door. In one example, an inner panel sub-assembly is produced off-line and then attached during one of the final steps of vehicle assembly. However, some portions of the inner panel sub-assembly are exposed to an occupant's view after assembly. Unfortunately, difficulty often arises when attempting to match the color of the components painted on-line with the color of the components painted off-line. Another design proposes the use of a separate door plate for mounting hardware such as the window regulator and the window glass. However, this design requires modification of the belt reinforcement structure of the inner door panel to allow for insertion of the window.

### SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a modular door assembly requiring less assembly time and effort at final assembly.

It is another object of the present invention to provide a structurally  
5 sound and cost effective modular door assembly for use in a motor vehicle.

It is yet another object of the present invention to provide a modular door exhibiting superior aesthetic appearance by removing the attachment fasteners from view.

According to the present invention, a vehicle door includes a door shell  
10 coupled to a door module. The door shell includes an outer panel secured to an inner panel to define a cavity therebetween, the inner panel having an opening communicating with the cavity. The door module includes a cassette, an interior trim panel coupled to the cassette, and an attachment mechanism for securing the door module to the door shell. The attachment mechanism is  
15 visually hidden during normal operation of the door. Finally, the cassette is cooperative with the inner panel to provide a positive rest position prior to securing the door module to the door shell.

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be  
20 understood however that the detailed description and specific examples, while indicating preferred embodiments of the invention, are intended for purposes of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

### BRIEF DESCRIPTION OF THE DRAWINGS

25 The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

Figure 1 is a partial exploded perspective view of a vehicle including a door constructed in accordance with the teachings of the present invention as  
30 viewed from the interior of the vehicle;

Figure 2 is an exploded perspective view of the door module;

Figure 3 is a simplified cross-sectional view of the vehicle door during assembly;

Figure 4 is an enlarged view of the upper attachment mechanism in cooperation with the door shell;

5        Figure 5 is an enlarged view of the lower attachment mechanism in cooperation with the door shell;

Figure 6 is a perspective view illustrating one of the steps performed during assembly;

10       Figure 7 is an enlarged view of the lower attachment mechanism during assembly;

Figure 8 is a perspective view illustrating the attachment of the lock rod during assembly;

Figure 9 is a perspective view illustrating attachment of the power window wiring harness;

15       Figure 10 is a partial cross-sectional view depicting the location of the door module of the present invention relative to the door shell during assembly;

Figure 11 is a perspective view of the vehicle door with the lower attachment mechanism fasteners exploded in alignment for assembly;

20       Figure 12 is a partial cross-sectional view depicting the window assembly attachment step of assembly;

Figure 13 is an exploded perspective view of the window assembly; and

Figure 14 is a simplified cross-sectional view of the completed modular door assembly of the present invention.

### **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

25       With reference to the drawings, a modular door constructed in accordance with the teachings of an embodiment of the present invention is generally identified at reference numeral 10. The modular door is shown operatively associated with an exemplary motor vehicle 12 having a door opening 14.

As particularly shown in Fig. 1, the modular door 10 is illustrated to generally include a door shell 16 and a door module 18. The door shell 16 includes an inner panel 20 and an outer panel 22 interconnected at their periphery to form a window frame 24 and a hollow cavity 26 separated by a belt reinforcement 28. The door shell 16 also includes a hinge (not shown) for swingingly mounting the door shell 16 on the body of the vehicle 12 in a conventional manner. The door module 18 includes a cassette 30 and an interior trim panel 32 which may be remotely constructed, connected to one another, and assembled to the vehicle 12 at a convenient time and location within the vehicle assembly line.

As a result of the modular nature of door 10, the door shell 16 may be mounted to the vehicle body during online assembly without the presence of the door module 18. This assembly method enables the door shell 16 to be painted along with the vehicle body thereby insuring uniformly colored panels. In addition, it should be noted that the door module 18 may be pre-assembled into one substantially integral unit ready for attachment at any point during the vehicle final assembly. Accordingly, the awkward, inconvenient attachment of door hardware through small access openings as discussed above is substantially eliminated. The vehicle manufacturer also benefits from lower inventory requirements and an improvement in overall product quality.

In reference to Fig. 1, the window frame 24 includes a forward channel 34 and a rearward channel 36 for guiding a window assembly 38 within the window frame 24. As is conventionally known, the window frame 24 also includes a suitable weather stripping for sealing the window assembly 38 to the window frame 24 when the window is in a raised or closed position. In addition, the inner panel 20 includes an enlarged opening 40 extending therethrough for providing access to the hollow cavity 26. The opening 40 is sized to permit installation of the door module 18 and, more particularly, to operatively accommodate the component operators mounted to the module such as the window operator and lock operator mechanisms.

To facilitate the modular assembly of door 10, door shell 16 includes a pair of hangers 42 located on and protruding from the inner panel 20. The

hangers 42 are generally upwardly opening "V" shaped devices defining a pocket 44. The hangers 42 are preferably located at or above an upper edge 46 of the opening 40 near the belt reinforcement 28. The inner panel 20 further includes a pair of guide slots 48 located at a lower peripheral edge 49 of the opening 40 to facilitate alignment of the door module 18 with the shell 16 as hereinafter described.

With reference to Fig. 2, the cassette 30 includes a plate 50 for mounting a variety of component operators 52 thereto. For example, the illustrated embodiment of the door module 18 includes a window operator 54 for controlling the vertical movement of the window assembly 38 in relation to the door shell 16 and a door operator 56 for selectively unlatching the door 10 from the vehicle body. The window operator 54 and the door operator 56 are each coupled to the plate 50. The window operator 54 depicted in the drawings includes an electric motor 58 driving a sector gear 60 coupled to a pair of window regulator arms 62. The window regulator arms 62 are provided with rollers 64 at their distal ends which cooperate with a generally "C" shaped channel 66 to vertically displace the channel 66 upon operation of the motor. A pair of snap receivers 68 are coupled to the channel 66 by a method known commonly in the art such as threaded fastening. As is described below with reference to Fig. 13, the snap receivers are adapted to receive cooperatively configured snaps for coupling the window assembly to the channel. It should be understood that the illustrated embodiment may be modified to accommodate other component operators, including other window operating and regulating devices, without departing from the scope of the present invention as defined by the appended claims.

The door operator 56 includes an inner door handle 70 pivotally coupled to a quick connect fitting 72 that is mounted to the plate 50. Fitting 72 is adapted to accept a lock rod 74 (Fig. 8) as will be described in greater detail hereinafter to allow connection of the door operator 56 to the appropriate door hardware. Other door operators may be used without departing from the scope of the invention as defined in the appended claims.

To achieve an aesthetically pleasing appearance, the interior trim panel 32 completely shields the cassette 30 from view once the door module 18 has been fixed to the door shell 16. In the illustrated embodiment, the interior trim panel 32 also includes a power window switch 76 (Fig. 1) having an integral wiring harness 78 (Fig. 2) terminating at a plug 80. In order to facilitate the electrical interconnection of the vehicle's battery (not shown) and the power window switch 76, the plug 80 and a portion of the wiring harness 78 is routed through an aperture (not shown) in the plate 50 and subsequently mounted thereto. The door module 18 is completed by connecting the interior trim panel 32 to the cassette 30 such as via composite fasteners 82. It should be appreciated that the method of interconnecting the interior trim panel 32 with the cassette 30 is merely exemplary and is not intended to limit the scope of the present invention.

With reference to Figs. 3 and 4, the door module 18 includes an upper attachment mechanism 84 having a pair of hooks 86 extending downwardly from an upper end 88 of the plate 50. Each of the hooks 86 is disposable in one of the pockets 44 to engage the hangers 42 and couple the door module 18 to the door shell 16.

As best seen in Figs. 2, 5 and 7, the door module 18 also includes a lower attachment mechanism 90 for interconnecting the door module 18 and the door shell 16. Specifically, the lower attachment mechanism 90 includes a pair of downwardly extending pivot brackets 92 coupled to a lower end 94 of the plate 50. Each of the pivot brackets 92 includes a tab 96 coupled to the inner panel 20, a skid plate 98 and a lip 100 which forms a seat 102 for cooperation with the guide slots 48 of the inner panel 20. Pivot bracket 92 further includes a generally planar flange 104 with an aperture 106 extending therethrough for receipt of a fastener 108. In the preferred embodiment, a weld nut 110 is secured to the flange 104 and aligned with the aperture 106 to facilitate a blind interconnection of the pivot bracket 92 with the door shell 16.

With reference to Figs. 6-14, the assembly sequence of the modular door of the present invention is described. As shown in Figs. 6 and 7, the door module 18 is initially positioned such that the pivot brackets 92 are disposed



within the guide slots 48 thereby aligning the interior trim panel 32 with the door shell 16. More particularly, the seats 102 of the pivot brackets 92 engage the guide slots 48 to provide a pivot point and a positive rest position. While the door module 18 is at the positive rest position shown in Fig. 8, an assembler connects the lock rod 74 with the quick connect fitting 72 to provide a mechanical connection between the inner door handle 70 and the door latch (not shown). Similarly, while the door module 18 is at the positive rest position, the plug 80 is connected to a vehicle power harness 112 as shown in Fig. 9. It should be appreciated that any number of components such as the lock rod 74 may be conveniently connected to an associated component operator such as inner door handle 70 while the door module 18 is at the positive rest position.

After the electrical and mechanical connections have been completed, the door module 18 is pivoted to position the hooks 86 above the pockets 44 as shown in Fig. 10. While the upper end 88 of the plate 50 is being held toward the belt reinforcement 28 to position the hooks 86 in coupling proximity to the hangers 42, an assembler forces a bottom portion 114 of the door module 18 towards the door shell 16. As such, the seats 102 are disengaged from the guide slots 48 and enter the cavity 26. Because the pivot brackets 92 are no longer supported by the inner panel, the door module 18 lowers such that the hooks 86 of the cassette 30 enter the pockets 44 thereby coupling the upper end 88 of the plate 50 to the inner panel 20 of door shell 16. One skilled in the art will appreciate that the pivot brackets 92 are configured such that the lip 100 and the skid plate 98 will ride in the guide slots 48 once the door module 18 is rotated to position the hooks 86 relative to the hangers 42 as earlier described. Accordingly, the pivot brackets 92 are allowed to enter the hollow cavity 26 until an inner surface 116 of the interior trim panel 32 engages an outer surface 118 of the inner panel 20. It should be appreciated that the apertures 106 are now positioned in alignment with apertures 119 extending through a bottom portion 120 of the inner panel 20.

Referring to Figs. 10 and 11, fasteners 108 are disposed within apertures 119 and rotated to threadingly engage the weld nuts 110 thereby coupling the lower end 94 of the cassette 30 to the door shell 16. Each of the

fasteners 108 is positioned to be visually hidden during normal operation of the vehicle 12. Specifically, the bottom portion 120 of the inner panel 20 is of significant width to shield the fasteners 108 from view.

Referring to Figs. 12 and 13, the assembly of modular door 10 is completed by constructing a window assembly 122 and inserting the window assembly 122 within the window frame 24 to blindly couple the window assembly to the window operator 54. One skilled in the art will appreciate that the method of blindly assembling the window assembly 122 to the modular door 10 allows a vehicle manufacturer to provide a modular door without sacrificing the structural integrity of the belt reinforcement 28.

The window assembly 122 includes a glass panel 124 and a pair of snaps 126. Each of the snaps 126 includes a pair of divergent panels 128 interconnected by a tapered plunger 130. The tapered plunger 130 includes a seat 132 for receiving a lower edge 134 of the glass panel 124. Each of the snaps 126 are fixed to the glass panel 124 using methods known in the art such as adhesive bonding or mechanical fastening. Each of the snap receivers 68 are preferably bolted to the channel 66 to allow service of the glass panel 124 after initial assembly. The snap receivers 68 include a pair of divergent, bifurcated legs 136 each terminating at an end 138 including a barb 140. Each of the barbs 140 include an engagement edge 142 which defines an effective insertion opening 144 having a dimension 146. One skilled in the art will appreciate that the effective insertion opening dimension 146 is smaller than the greatest width of the tapered plunger 130. Accordingly, as the window assembly 122 is inserted into the window frame 24, the tapered plunger 130 biasedly engages the bifurcated legs 136. The tapered plunger 130 is further axially disposed toward the snap receiver 68 until the barb 140 engages a retention plane 148 of the tapered plunger thereby creating a snap-fit coupling as shown in Fig. 14. Specifically, the barb 140 and the retention plane 148 compliment each other such that an axial force in an upward direction will not separate the window assembly 122 from the window operator 54 after the snap-fit operation has been completed. Accordingly, if service is desired, a technician must remove at least a portion of the interior trim panel 32 and

disconnect the snap receivers 68 from the channel 66. At this time, the window assembly 122 may be removed from the window frame 24.

Therefore, it should be appreciated that the configuration and operation of the modular door 10 provides both manufacturing and functional advantages over the prior art. Specifically, the modular configuration of the present invention reduces the cost and time required to assemble a door on the vehicle production line. Additionally, the blind attachment of the window assembly 38 provides for an uninterrupted, structurally robust, belt reinforcement.

The foregoing discussion discloses and describes merely exemplary embodiments of the present invention. One skilled in the art will readily recognize from such discussion, and from the accompanying drawings and claims, that various changes, modifications and variations may be made therein without department from the spirit and scope of the invention as defined in the following claims:

**What Is Claimed Is:**

1. A vehicle door comprising:

a door shell including an outer panel secured to an inner panel, said inner panel having an opening therein, said door shell defining a hollow cavity; and

5 a door module including a cassette and an interior trim panel coupled to said cassette, said door module further including an attachment mechanism for securing said door module to said door shell, said attachment mechanism being visually hidden during normal operation of the door, said cassette cooperative with said inner panel to provide a positive rest position prior to  
10 securing said door module to said door shell.

2. The vehicle door of Claim 1 wherein said cassette includes a plate adapted to operatively receive a component operator.

3. The vehicle door of Claim 2 wherein said positive rest position places a said component operator in coupling proximity to a door component.

15 4. The vehicle door of Claim 2 wherein component operator includes a door actuator adapted for selectively unlatching said door from a vehicle body and wherein said door component includes a lock rod.

5. The vehicle door of Claim 2 wherein said cassette includes a quick connect wiring harness adapted to electrically interconnect a power  
20 source and said component operator.

6. The vehicle door of Claim 1 wherein said attachment mechanism includes an upper attachment mechanism having a hanger extending from said inner panel and a hook extending from said cassette, said hanger and said hook cooperating to secure said door module to said door shell.

7. The vehicle door of Claim 6 wherein said hanger includes an upwardly opening clasp integrally formed within said inner panel.

8. The vehicle door of Claim 1 wherein said attachment mechanism includes a lower attachment mechanism having a pivot bracket with a tab  
5 coupled to one of said inner and outer panels.

9. The vehicle door of Claim 8 wherein said tab includes a lip which forms a seat cooperative with a portion of said inner panel.

10. The vehicle door of Claim 8 wherein said tab includes a flange having an aperture adapted to receive a fastener for coupling said door module  
-10 to said door shell.

11. The vehicle door of Claim 8 wherein said tab downwardly extends from said cassette and cooperates with a recess formed in said inner panel to align said door module with said door shell.

12. The vehicle door of Claim 1 wherein said cassette includes a  
15 snap receiver disposed in said inner panel opening for accepting said window assembly.

13. The vehicle door of Claim 12 wherein said window assembly includes a snap engaging said snap receiver.

14. A door module adapted to be coupled to a door shell having an  
20 outer panel secured to an inner panel, the door shell defining a hollow cavity, the inner panel having an opening communicating with the hollow cavity, said door module comprising:

an interior trim panel;

a cassette coupled to said interior trim panel, said cassette including an  
25 attachment mechanism adapted to couple said door module to the door shell,

said door module adapted to receive a window assembly after said door module is secured to said door shell.

15. The door module of Claim 14 wherein said cassette includes a plate adapted to receive a window operator for controlling the movement of said window assembly relative to said door shell.

16. The door module of Claim 15 wherein said window operator engages said window assembly in a snap-fit connection.

17. A method for assembling a door:  
creating a door shell having an inner panel and an outer panel defining a belt reinforcement and a hollow cavity;  
creating a door module;  
resting said door module on said door shell at a positive rest position;  
connecting a door component to said door module;  
pivoting said door module relative to said door shell to position an attachment mechanism in coupling position relative to said inner panel of said door shell;  
lowering said door module to couple said door module to said door shell at an upper location; and  
fastening said door module to said door shell at a lower location.

18. The method for assembling a door of Claim 17 wherein said attachment mechanism includes a hook protruding from said door module wherein said hook engages a hanger coupled to said inner panel of said door shell.


19. The method of assembling a door of Claim 17 wherein said door module includes a cassette and an interior trim panel coupled to said cassette, said cassette having a plate adapted to receive a component operator.

20. The method of Claim 16 further including the steps of inserting a window assembly into said hollow cavity and coupling said window assembly to said cassette after the step of fastening said door module to said door.


21. A window assembly adapted to be coupled to a door shell having a belt reinforcement and a window frame above the belt reinforcement, the belt reinforcement having a slot adapted to receive a window panel and the window frame defining a peripheral track communicating with the slot, said window assembly comprising:


snaps coupled to said window panel; and  
receivers adapted to accommodate said snaps in coupling engagement, said receivers operatively associated with a window operator.

22. The window assembly of Claim 21 wherein said snaps are engaged with said receivers after an interior trim panel is coupled to the door shell.

Fig-1










Fig-4




Fig-5









Fig-7

Fig-6










Fig-11



Fig-12

Fig-13



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 May 2001 (10.05.2001)

PCT

(10) International Publication Number  
**WO 01/32456 A3**

(51) International Patent Classification<sup>7</sup>: **B60J 5/04**

(21) International Application Number: PCT/US00/41661

(22) International Filing Date: 27 October 2000 (27.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/433,912 3 November 1999 (03.11.1999) US

(71) Applicant: **THE BUDD COMPANY** [US/US]; 3155  
West Big Beaver Road, Troy, MI 48084 (US).

(72) Inventors: **PACELLA, John, P.**; 2997 Rhineberry,  
Rochester Hills, MI 48309 (US). **MROZOWSKI, Joseph,**

E.: 6852 North Crest Way East, Clarkston, MI 48346 (US).  
**MERCIER, Larry, A., Jr.**; 6430 Dewey Drive, Troy, MI  
48098 (US).


(74) Agents: **SCHIVLEY, G., Gregory et al.**; Harness, Dickey  
& Pierce, P.L.C., P.P. Box 828, Bloomfield Hills, MI 48303  
(US).

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ,  
BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK,  
DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL,  
IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU,  
LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT,  
RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA,  
UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: MODULAR DOOR



(57) Abstract: A door (10) includes a door shell (16) coupled to a door module (18). The door shell (16) includes an outer panel (22) secured to an inner panel (20), the inner panel (20) having an opening therein. The door shell (16) defines a hollow cavity. The door module (18) includes a cassette (30) and an interior trim panel (32) coupled to the cassette (30). The door module (18) further includes an attachment mechanism (84, 90) for securing the door module (18) to the door shell (16). The attachment mechanism (84, 90) is visually hidden during normal operation of the door (10). The cassette (30) is cooperative with the inner panel (20) to provide a positive rest position prior to securing the door module (18) to the door shell (16).

WO 01/32456 A3

WO 01/32456 A3



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:  
6 December 2001

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/41661

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B60J5/04

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 195 26 367 A (KUESTER & CO GMBH) 22 February 1996 (1996-02-22) figures 1-5	1-3, 14, 15, 17
X	DE 197 55 450 C (BROSE FAHRZEUGTEILE) 15 April 1999 (1999-04-15) figures 1,2	1-3, 14, 15 17
A	US 5 927 020 A (KOBREHEL MICHAEL D) 27 July 1999 (1999-07-27) figures 1-4	1-3, 14, 15 17
X	EP 0 286 923 A (BUDD CO) 19 October 1988 (1988-10-19) figures 1-4	1-3, 14, 15 17
A		
	--- -/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

\*A\* document defining the general state of the art which is not considered to be of particular relevance

\*E\* earlier document but published on or after the international filing date

\*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

\*O\* document referring to an oral disclosure, use, exhibition or other means

\*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\*&amp;\* document member of the same patent family

Date of the actual completion of the international search

27 April 2001

Date of mailing of the international search report

11/05/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Thomas, C

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/41661

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A	FR 2 776 965 A (MERITOR LIGHT VEHICLE SYS LTD) 8 October 1999 (1999-10-08) figures 1-7 ----	1-3, 14, 15 17
A	WO 97 45283 A (LEAR CORP ; EMERLING DAVID M (US); DIMIG STEVEN J (US); MORRISON GE) 4 December 1997 (1997-12-04) figures 1-5 ----	1, 14, 17
A	EP 0 694 427 A (MECAPLAST SAM) 31 January 1996 (1996-01-31) figures 1-5 -----	1, 14, 17

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/41661

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 19526367 A	22-02-1996	NONE	
DE 19755450 C	15-04-1999	NONE	
US 5927020 A	27-07-1999	NONE	
EP 0286923 A	19-10-1988	US 4785585 A BR 8801723 A DE 3871427 A JP 63279926 A	22-11-1988 16-11-1988 02-07-1992 17-11-1988
FR 2776965 A	08-10-1999	NONE	
WO 9745283 A	04-12-1997	US 5904002 A AU 3475897 A DE 19781793 T EP 0901420 A GB 2328911 A, B	18-05-1999 05-01-1998 27-05-1999 17-03-1999 10-03-1999
EP 0694427 A	31-01-1996	DE 4426426 A JP 8175171 A	15-02-1996 09-07-1996